



Rubrik Complete Edition

Powerful, Affordable and Easy-to-Use

Rubrik simplifies backup and instant recovery across hybrid cloud environments. It eliminates legacy backup complexity by integrating data orchestration, catalog management, and continuous data protection into a single software platform. With Rubrik, companies can deliver near-zero RTOs with predictive search, unlock cloud for long-term data retention, and recover instantly from ransomware with immutable backups native to the platform.

Rubrik Complete Edition delivers the enterprise-grade functionality of Rubrik Cloud Data Management software, packaged to be affordable. With a single Rubrik Complete Edition subscription license, you can migrate licenses into the cloud at any time. Keep your data center modern for the hybrid cloud era with peace of mind.

Rubrik Complete Edition Pro further helps you increase your resiliency against ransomware, making it easier and faster to recover from an attack. With a simple, intuitive user interface that tracks how your data changed over time, Polaris Radar as part of Complete Edition Pro helps you quickly identify what was impacted where, and restore to the most recent version with just a few clicks.



GET UP AND RUNNING

Set up in about 15 minutes with Rubrik's plug and play appliances. Determine what policies to apply. Rubrik takes care of the rest.



RECOVER FROM RANSOMWARE

Protect from ransomware with natively immutable backups that can't be encrypted or deleted. Identify anomalies, see what data has been impacted and restore to the most clean state with Polaris Radar.



NEAR-ZERO RTO AND RPO

Avoid data loss and minimize downtime with continuous data protection and instant recovery.

OVERVIEW OF RUBRIK COMPLETE EDITION SOFTWARE

	COMPLETE EDITION Backup & Recovery with Cloud Archival	COMPLETE EDITION PRO Backup & Recovery with Ransomware Protection
Cloud Data Management Backup & recovery, replication, search, analytics, and copy data management across hybrid clouds.	✓	✓
Polaris GPS A centralized platform to manage global, distributed Rubrik environments.	✓	✓
CloudOut Cloud archival for long-term retention.	✓	✓
Continuous Data Protection (5 VMs per node) Natively integrated data protection offering a continuous stream of recovery points for near-zero RPOs.	✓	✓
CloudOn Instantiation of on-premises workloads in public cloud.		✓
Polaris Radar Ransomware recovery with deep intelligence on threat behavior and impact.		✓
M365 Protection Search, discover, safeguard and recover M365 data hosted on Rubrik Polaris platform.	\$	\$

HOW RUBRIK COMPLETE EDITION WORKS

Rubrik Complete Edition is offered as a 3-year minimum subscription that includes software, hardware and Basic Support (M-F 8am-8pm). All Rubrik Complete Edition licenses can be transferred to the cloud during the term of the subscription at no additional license cost. Cloud licenses in Rubrik Complete Edition are eligible only for cloud migration use cases. Rubrik Complete Edition renewal prices are predictable, which means no surprises at renewal time.



Rubrik Standard Flash Appliance Specifications

Rubrik Cloud Data Management Platform



Rubrik r6404s
Growing Environments



Rubrik r6408s
Enterprise Environments

APPLIANCE SPECIFICATIONS		
Model	r6404s ¹	r6408s ¹
CPU	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz
Memory	256GB DDR4	384GB DDR4
Storage	12 x 4TB HDD	12 x 8TB HDD
	4 x 400GB SSD	4 x 400GB SSD
Network Connections	4 Dual-Port x 10GbE/25GbE (data) ³ 4 Dual-Port x 10GBase-T (mgmt) 4 x 1GBase-T (IPMI)	4 Dual-Port x 10GbE/25GbE (data) ³ 4 Dual-Port x 10GBase-T (mgmt) 4 x 1GBase-T (IPMI)

¹Software-based encryption included, ²FIPS 140-2 Level 2 self-encrypting drive, ³Available in SFP+ 10GbE/25GbE or 10GBase-T

PHYSICAL & ENVIRONMENTAL SPECIFICATIONS		
Model	r6404s	r6408s
Dimensions	2U Rackmount Height: 3.5" (88mm) Width: 17.6" (447mm) Depth: 30.5" (775mm)	
Weight Net Weight includes HDD/ SSDs. Gross Weight includes packaging and rails.	Gross Weight: 113.0 lbs (51.3 kg) Net Weight: 86.0 lbs (39.0 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)
System Cooling	4 x 8 cm heavy duty PWM fans with optimal fan speed control	
Operating Environment	Op Temp: 10°C to 35°C (50°F to 95°F), Non-Op Temp: -40°C to 70°C (-40°F to 158°F), Op Humidity (non-condensing): 8% to 90%, Non-Op Humidity (non-condensing): 5% to 95%	
Power Supply	1200-2090W @ 100-240V / 14-9.8A, 50-60Hz Dual Supply for Redundancy/Hot-Pluggable	
Max Power Consumption	1023 Watts	985 Watts
Max Thermal Dissipation	3490 BTU/hour	3361 BTU/hour
Operating Requirements	Input Voltage: 100-240V AC auto-range, Input Frequency: 50-60Hz	

MODEL NAMING CONVENTION

