

Rubrik Standard Flash Appliance Specifications

Rubrik Cloud Data Management Platform



Rubrik r6304s
Small Environments



Rubrik r6404s
Growing Environments



Rubrik r6408s
Enterprise Environments



Rubrik r6410s
Large-scale Environments



Rubrik r6412s
Large-scale Environments



Rubrik r6408f
Higher Security Standards

APPLIANCE SPECIFICATIONS

Model	r6304s ¹	r6404s ¹	r6408s ¹	r6410s ¹	r6412s ¹	r6408f
CPU	3 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz
Memory	192GB DDR4	256GB DDR4	384GB DDR4	384GB DDR4	384GB DDR4	384GB DDR4
Storage	9 x 4TB HDD	12 x 4TB HDD	12 x 8TB HDD	12 x 10TB HDD	12 x 12TB HDD	12 x 8TB HDD ²
	3 x 400GB SSD	4 x 400GB SSD	4 x 400GB SSD	4 x 400GB SSD	4 x 400GB SSD	4 x 400GB SSD ²
Network Connections	3 Dual-Port x 10GbE/25GbE (data) ³	4 Dual-Port x 10GbE/25GbE (data) ³	4 Dual-Port x 10GbE/25GbE (data) ³	4 Dual-Port x 10GbE/25GbE (data) ³	4 Dual-Port x 10GbE/25GbE (data) ³	4 Dual-Port x 10GbE/25GbE (data) ³
	3 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)
	3 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)

¹Software-based encryption included, ²FIPS 140-2 Level 2 self-encrypting drive, ³Available in SFP+ 10GbE/25GbE or 10GBase-T

PHYSICAL & ENVIRONMENTAL SPECIFICATIONS

Model	r6304s	r6404s	r6408s	r6410s	r6412s	r6408f
Dimensions	2U Rackmount Height: 3.5" (88mm) Width: 17.6" (447mm) Depth: 30.5" (775mm)					
Weight Net Weight includes HDD/SSDs. Gross Weight includes packaging and rails.	Gross Weight: 102.0 lbs (46.2 kg) Net Weight: 75.0 lbs (34.0 kg)	Gross Weight: 113.0 lbs (51.3 kg) Net Weight: 86.0 lbs (39.0 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)	Gross Weight: 116.0 lbs (53.0 kg) Net Weight: 89.0 lbs (40.7 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)
System Cooling	4 x 8 cm heavy duty PWM fans with optimal fan speed control					
Operating Environment	Op Temp: 10°C to 35°C (50°F to 95°F), Non-Op Temp: -40°C to 70°C (-40°F to 158°F), Op Humidity (non-condensing): 8% to 90%, Non-Op Humidity (non-condensing): 5% to 95%					
Power Supply	1200-2090W @ 100-240V / 14-9.8A, 50-60Hz Dual Supply for Redundancy/Hot-Pluggable					
Max Power Consumption	836 Watts	1023 Watts	985 Watts	985 Watts	985 Watts	985 Watts
Max Thermal Dissipation	2853 BTU/hour	3490 BTU/hour	3361 BTU/hour	3361 BTU/hour	3361 BTU/hour	3361 BTU/hour
Operating Requirements	Input Voltage: 100-240V AC auto-range, Input Frequency: 50-60Hz					

MODEL NAMING CONVENTION

