


# Rubrik Enhanced Flash Appliance Specifications


## Rubrik Cloud Data Management Platform



**Rubrik r6304se**  
Small Environments



**Rubrik r6404se**  
Growing Environments



**Rubrik r6408se**  
Enterprise Environments



**Rubrik r6410se**  
Large-scale Environments



**Rubrik r6412se**  
Large-scale Environments

### APPLIANCE SPECIFICATIONS

Model	r6304se <sup>1</sup>	r6404se <sup>1</sup>	r6408se <sup>1</sup>	r6410se <sup>1</sup>	r6412se <sup>1</sup>
CPU	3 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz	4 x 10-Core x86 2.2 GHz
Memory	192GB DDR4	256GB DDR4	384GB DDR4	384GB DDR4	384GB DDR4
Storage	9 x 4TB HDD	12 x 4TB HDD	12 x 8TB HDD	12 x 10TB HDD	12 x 12TB HDD
	3 x 3.8TB SSD	4 x 3.8TB SSD	4 x 3.8TB SSD	4 x 3.8TB SSD	4 x 3.8TB SSD
Network Connections	3 Dual-Port x 10GbE/25GbE (data) <sup>3</sup>	4 Dual-Port x 10GbE/25GbE (data) <sup>3</sup>	4 Dual-Port x 10GbE/25GbE (data) <sup>3</sup>	4 Dual-Port x 10GbE/25GbE (data) <sup>3</sup>	4 Dual-Port x 10GbE/25GbE (data) <sup>3</sup>
	3 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)	4 Dual-Port x 10GBase-T (mgmt)
	3 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)	4 x 1GBase-T (IPMI)

<sup>1</sup>Software-based encryption included, <sup>2</sup>FIPS 140-2 Level 2 self-encrypting drive, <sup>3</sup>Available in SFP+ 10GbE/25GbE or 10GBase-T

### PHYSICAL & ENVIRONMENTAL SPECIFICATIONS

Model	r6304se	r6404se	r6408se	r6410se	r6412se
Dimensions	2U Rackmount Height: 3.5" (88mm) Width: 17.6" (447mm) Depth: 30.5" (775mm)				
Weight Net Weight includes HDD/ SSDs. Gross Weight includes packaging and rails.	Gross Weight: 102.0 lbs (46.2 kg) Net Weight: 75.0 lbs (34.0 kg)	Gross Weight: 113.0 lbs (51.3 kg) Net Weight: 86.0 lbs (39.0 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)	Gross Weight: 115.0 lbs (52.0 kg) Net Weight: 88.0 lbs (39.9 kg)	Gross Weight: 116.0 lbs (53.0 kg) Net Weight: 89.0 lbs (40.7 kg)
System Cooling	4 x 8 cm heavy duty PWM fans with optimal fan speed control				
Operating Environment	Op Temp: 10°C to 35°C (50°F to 95°F), Non-Op Temp: -40°C to 70°C (-40°F to 158°F), Op Humidity (non-condensing): 8% to 90%, Non-Op Humidity (non-condensing): 5% to 95%				
Power Supply	1200-2090W @ 100-240V / 14-9.8A, 50-60Hz Dual Supply for Redundancy/Hot-Pluggable				
Max Power Consumption	836 Watts	1023 Watts	985 Watts	985 Watts	985 Watts
Max Thermal Dissipation	2853 BTU/hour	3490 BTU/hour	3361 BTU/hour	3361 BTU/hour	3361 BTU/hour
Operating Requirements	Input Voltage: 100-240V AC auto-range, Input Frequency: 50-60Hz				

### MODEL NAMING CONVENTION

